

Package: lspls (via r-universe)

September 3, 2024

Title LS-PLS Models

Version 0.2-2

Date 2018-07-26

Author Bjørn-Helge Mevik [aut, cre]

Maintainer Bjørn-Helge Mevik <b-h@mevik.net>

Encoding UTF-8

Depends pls (>= 2.2.0)

Imports grDevices, graphics, methods, stats

Description Implements the LS-PLS (least squares - partial least squares) method described in for instance Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) ``A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables" Journal of Chemometrics, 18(10), 451--464, <doi:10.1002/cem.890>.

License GPL-2

URL <http://mevik.net/work/software/lspls.html>,
<https://github.com/bhmevik/lspls>

BugReports <https://github.com/bhmevik/lspls/issues>

Repository <https://bhmevik.r-universe.dev>

RemoteUrl <https://github.com/bhmevik/lspls>

RemoteRef HEAD

RemoteSha af5bf5e2bf0ca27c59ca774a092edc9db1e6db1e

Contents

lspls-package	2
lspls	4
lsplsCv	6
MSEP.lsplsCv	8
orthlspls.fit	9

orthlsplsCv	10
plot.lspls	11
plot.lsplsCv	12
predict.lspls	13
projections	14
Index	16

lspls-package	<i>LS-PLS Models</i>
---------------	----------------------

Description

Implements the LS-PLS (least squares - partial least squares) method described in for instance Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) "A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables" Journal of Chemometrics, 18(10), 451–464, <doi:10.1002/cem.890>.

Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.

LS-PLS (least squares–partial least squares) models are written on the form

$$Y = X\beta + T_1\gamma_1 + \cdots + T_k\gamma_k + E,$$

where the terms T_i are one or more matrices $Z_{i,j}$ separated by a colon (:), i.e., $Z_{i,1} : Z_{i,2} : \cdots : Z_{i,l_i}$. Multi-response models are possible, in wich case Y should be a matrix.

The model is fitted from left to right. First Y is fitted to X using least squares (LS) regression and the residuals calculated. For each i , the matrices $Z_{i,1}, \dots, Z_{i,l_i}$ are orthogonalised against the variables used in the regression sofar (when $i = 1$, this means X). The residuals from the LS regression are used as the response in PLS regressions with the orthogonalised matrices as predictors (one PLS regression for each matrix), and the desired number of PLS components from each matrix are included among the LS prediction variables. The LS regression is then refit with the new variables, and new residuals calculated.

The function to fit LS-PLS models is `lspls`. A typical usage to fit the model

$$y = X\beta + Z\gamma + V_1 : V_2\eta + W\theta + E$$

would be

```
mod <- lspls(y ~ X + Z + V1:V2 + W, ncomp = list(3, c(2,1), 2),
            data = mydata)
```

The first argument is the formula describing the model. X is fit first, using LS. Then PLS scores from Z (orthogonalised) are added. Then PLS scores from $V1$ and $V2$ are added (simultaneously), and finally PLS scores from W . The next argument, `ncomp`, specifies the number of components to use from each PLS: 3 Z score vectors, 2 $V1$ score vectors, 1 $V2$ score vector and 2 W score vectors. Finally, `mydata` should be a data frame with matrices y , X , Z , $V1$, $V2$ and W (for single-response models, y can be a vector).

Currently, score plots and loading plots of fitted models are implemented. `plot(mod, "scores")` gives score plots for each PLS regression, and `plot(mod, "loadings")` gives loading plots.

There is a `predict` method to predict response or score values from new data

```
predict(mod, newdata = mynewdata)
```

(This predicts response values. Use `type = "scores"` to get scores.) Also, the standard functions `resid` and `fitted` can be used to extract the residuals and fitted values.

In order to determine the number of components to use from each matrix, one can use cross-validation:

```
cvmod <- lsplsCv(y ~ X + Z + V1:V2 + W, ncomp = list(4, c(3,4), 3),  
               segments = 12, data = mydata)
```

In `lsplsCv`, `ncomp` gives the maximal number of components to test. The argument `segments` specifies the number of segments to use. One can specify the type of segments to use (random (default), consecutive or interleaved) with the argument `segment.type`. Alternatively, one can supply the segments explicitly with `segments`. See [lsplsCv](#) for details.

One can plot cross-validated RMSEP values with `plot(cvmod)`. (Similarly, `plot(cvmod, "MSEP")` plots MSEP values.) This makes it easier to determine the optimal number of components for each PLS. See [plot.lsplsCv](#) for details. To calculate the RMSEP or MSEP values explicitly, one can use the function `RMSEP` or `MSEP`.

Author(s)

Bjørn-Helge Mevik [aut, cre]

Maintainer: Bjørn-Helge Mevik <b-h@mevik.net>

References

Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables. *Journal of Chemometrics*, **18**(10), 451–464.

Jørgensen, K., Mevik, B.-H., Næs, T. Combining Designed Experiments with Several Blocks of Spectroscopic Data. (Submitted)

Mevik, B.-H., Jørgensen, K., Måge, I., Næs, T. LS-PLS: Combining Categorical Design Variables with Blocks of Spectroscopic Measurements. (Submitted)

See Also

[lspls](#), [lsplsCv](#), [plot.lspls](#), [plot.lsplsCv](#)

Examples

```
## FIXME
```

 lspls

Fit LS-PLS Models

Description

A function to fit LS-PLS (least squares–partial least squares) models.

Usage

```
lspls(formula, ncomp, data, subset, na.action, model = TRUE, ...)
```

Arguments

formula	model formula. See Details.
ncomp	list or vector of positive integers, giving the number of components to use for each ‘pls-matrix’. See Details.
data	an optional data frame with the data to fit the model from.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
na.action	a function which indicates what should happen when the data contain missing values.
model	logical. If TRUE, the model frame is returned.
...	additional arguments, passed to the underlying PLSR fit function.

Details

lspls fits LS-PLS models, in which matrices are added successively to the model. The first matrix is fit with ordinary least squares (LS) regression. The rest of the matrices are fit with partial least squares regression (PLSR), using the residuals from the preceding model as response. See [lspls-package](#) or the references for more details, and [lspls-package](#) for typical usage.

The model formula is specified as $resp \sim term1 + term2 + \dots$. If *resp* is a matrix (with more than one column), a multi-response model is fitted. *term1* specifies the first matrix to be fitted, using LS. Each of the remaining terms will be added sequentially in the order specified in the formula (from left to right). Each term can either be a single matrix, which will be added by itself, or several matrices separated with `:`, e.g., `Z:V:W`, which will be added simultaneously (these will be denoted *parallel* matrices).

The first matrix, *term1*, is called the *LS matrix*, and the rest of the predictor matrices (whether parallel or not) are called *PLS matrices*.

Note that an intercept is *not* automatically added to the model. It should be included as a constant column in the LS matrix, if desired. (If no intercept is included, the PLS matrices should be centered. This happens automatically if the LS matrix includes the intercept.)

The number of components to use in each of the PLSR models is specified with the `ncomp` argument, which should be a list. Each element of the list gives the number of components to use for the corresponding term in the formula. If the term specifies parallel matrices (separated with `:`), the list element should be a vector with one integer for each matrix. Otherwise, it should be a number.

To simplify the specification of `ncomp`, the following conversions are made: if `ncomp` is a vector, it will be converted to a list. `ncomp` will also be recycled as necessary to get one element for each term. Finally, for a parallel term, the list element will be recycled as needed. Thus, `ncomp = 4` will result in 4 components being fit for every PLS matrix.

Currently, the function `lspls` itself handles the formula and the data, and calls the underlying fit function `orthlspls.fit` to do the actual fitting. This implements the orthogonalized version of the LS-PLS algorithm, and without splitting of parallel matrices into common and unique components (see the references). Extensions to non-orthogonalized algorithms, and splitting of parallel matrices are planned.

Value

An object of class "lspls". The object contains all components returned by the underlying fit function (currently `orthlspls.fit`). In addition, it contains the following components:

<code>fitted.values</code>	matrix with fitted values, one column per response
<code>na.action</code>	if observations with missing values were removed, <code>na.action</code> contains a vector with their indices.
<code>ncomp</code>	the list of number of components used in the model.
<code>call</code>	the function call.
<code>terms</code>	the model terms.
<code>model</code>	if <code>model = TRUE</code> , the model frame.

Note

The user interface (e.g. the model handling) is experimental, and might well change in later versions.

The handling of formula (especially `:`) is non-standard. Note that the order of the terms is significant; terms are added from left to right.

Author(s)

Bjørn-Helge Mevik

References

- Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables. *Journal of Chemometrics*, **18**(10), 451–464.
- Jørgensen, K., Mevik, B.-H., Næs, T. Combining Designed Experiments with Several Blocks of Spectroscopic Data. (Submitted)
- Mevik, B.-H., Jørgensen, K., Måge, I., Næs, T. LS-PLS: Combining Categorical Design Variables with Blocks of Spectroscopic Measurements. (Submitted)

See Also

[lspls-package](#), [lsplsCv](#), [plot.lspls](#)

Examples

```
##FIXME
```

lsplsCv	<i>Cross-Validate LS-PLS Models</i>
---------	-------------------------------------

Description

Calculate cross-validated predictions for LS-PLS models.

Usage

```
lsplsCv(formula, ncomp, data, subset, na.action, segments = 10,
         segment.type = c("random", "consecutive", "interleaved"),
         length.seg, model = TRUE, ...)
```

Arguments

formula	model formula. See Details.
ncomp	list or vector of positive integers, giving the number of components to use for each PLS matrix. See Details.
data	an optional data frame with the data to fit the model from.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
na.action	a function which indicates what should happen when the data contain missing values.
segments	the number of segments to use, or a list with segments (see Details).
segment.type	the type of segments to use. Ignored if segments is a list.
length.seg	Positive integer. The length of the segments to use. If specified, it overrides segments unless segments is a list.
model	logical. If TRUE, the model frame is returned.
...	additional arguments, passed to the underlying cross-validation function (currently orthlsplsCv).

Details

The function performs a cross-validation, using the model and segments specified in the call. It returns an object of class "lsplsCv", which has a plot method (see [plot.lsplsCv](#)). See [lspls-package](#) for typical usage and more about LS-PLS models.

See [lspls](#) for details about specifying the model with formula and ncomp. Note that lsplsCv cross-validates models with from 0 components to the numbers of components specified with ncomp.

If segments is a list, the arguments segment.type and length.seg are ignored. The elements of the list should be integer vectors specifying the indices of the segments. See [cvsegments](#) for details.

Otherwise, segments of type segment.type are generated. How many segments to generate is selected by specifying the number of segments in segments, or giving the segment length in length.seg. If both are specified, segments is ignored.

Value

An object of class "lsplsCv", with components

pred	the cross-validated predictions. An array with one dimension for the observations, one for the responses, and one for each of the PLS matrices.
segments	the list of segments used in the cross-validation.
na.action	if observations with missing values were removed, na.action contains a vector with their indices.
ncomp	the list of number of components used in the model.
call	the function call.
terms	the model terms.
model	if model = TRUE, the model frame.

Note

Currently, lsplsCv handles the formula and the data, and calls [orthlsplsCv](#) for the actual cross-validation. The formula interface is experimental, and might change in future versions.

Author(s)

Bjørn-Helge Mevik

References

Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables. *Journal of Chemometrics*, **18**(10), 451–464.

Jørgensen, K., Mevik, B.-H., Næs, T. Combining Designed Experiments with Several Blocks of Spectroscopic Data. (Submitted)

Mevik, B.-H., Jørgensen, K., Måge, I., Næs, T. LS-PLS: Combining Categorical Design Variables with Blocks of Spectroscopic Measurements. (Submitted)

See Also

[lspls](#), [plot.lsplsCv](#), [cvsegments](#), [orthlsplsCv](#), [lspls-package](#)

Examples

```
##FIXME
```

MSEP.lsplsCv

MSEP, RMSEP and R² for LS-PLS

Description

(Root) Mean Squared Error of Prediction ((R)MSEP) and R^2 methods for LS-PLS cross-validations ("lsplsCv" objects).

Usage

```
## S3 method for class 'lsplsCv'
MSEP(object, scale = FALSE, ...)
## S3 method for class 'lsplsCv'
RMSEP(object, scale = FALSE, ...)
## S3 method for class 'lsplsCv'
R2(object, ...)
```

Arguments

object	an "lsplsCv" object, typically the output from lsplsCv.
scale	logical. Whether the responses and predicted values should be divided by the standard deviation of the response prior to calculating the measure. This is most useful when comparing several responses. Default is not to scale. Note that this argument is ignored by the R2 method, since R^2 is independent of scale.
...	Further arguments. Currently unused.

Value

An array. The first dimension corresponds to the responses (for single-response models, the length of this dimension is 1). The rest of the dimensions correspond to the number of components from the PLS matrices.

Author(s)

Bjørn-Helge Mevik

See Also

[lsplsCv](#), [plot.lsplsCv](#)

orthpls.fit *Underlying LS-PLS Fit Function*

Description

Fits orthogonalized LS-PLS models.

Usage

```
orthpls.fit(Y, X, Z, ncomp)
```

Arguments

Y	matrix. Response matrix.
X	matrix. The first predictor matrix (typically a design matrix).
Z	list. List of predictor matrices.
ncomp	list. The number of components to fit from each matrix.

Details

orthpls.fit is not meant to be called by the user. It is called by [lspls](#) to do the actual fitting. See [lspls](#) for details about LS-PLS and ncomp. Each element of the list Z should either be a matrix or a list of matrices.

Value

A list with components

coefficients	matrix with the final prediction coefficients
predictors	matrix with variables and scores used in the final regression
orthCoefs	list of coefficient generating matrices, to be used when predicting new predictors.
models	list of fitted PLS models for the matrices
ncomp	list with the number of components used
scores	list of score matrices
loadings	list of loading matrices
residuals	matrix with fit residuals, one column per response

Note

The interface (arguments and return values) is likely to change in a future version.

Author(s)

Bjørn-Helge Mevik

References

Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables. *Journal of Chemometrics*, **18**(10), 451–464.

Jørgensen, K., Mevik, B.-H., Næs, T. Combining Designed Experiments with Several Blocks of Spectroscopic Data. (Submitted)

Mevik, B.-H., Jørgensen, K., Måge, I., Næs, T. LS-PLS: Combining Categorical Design Variables with Blocks of Spectroscopic Measurements. (Submitted)

See Also

[lpls](#)

orthplsCv

Low Level Cross-Validation Function

Description

Low-level function to perform the cross-validation in `lplsCv`.

Usage

```
orthplsCv(Y, X, Z, ncomp, segments, trace = FALSE, ...)
```

Arguments

Y	matrix. Response matrix.
X	matrix. The first predictor matrix (typically a design matrix).
Z	list. List of predictor matrices.
ncomp	list. The number of components to fit from each matrix.
segments	list. The segments to use.
trace	logical; if TRUE, the segment number is printed for each segment.
...	Further arguments. Currently not used.

Details

This function is not meant to be called directly by the user. It performs cross-validation of orthogonalized LS-PLS-models without splitting of parallel matrices into common and unique components. See the references for details.

Value

An array of cross-validated predictions. The first dimension corresponds to the observations, the second to the responses, and the rest to the number of components of the PLS models.

Author(s)

Bjørn-Helge Mevik

References

Jørgensen, K., Segtnan, V. H., Thyholt, K., Næs, T. (2004) A Comparison of Methods for Analysing Regression Models with Both Spectral and Designed Variables. *Journal of Chemometrics*, **18**(10), 451–464.

Jørgensen, K., Mevik, B.-H., Næs, T. Combining Designed Experiments with Several Blocks of Spectroscopic Data. (Submitted)

Mevik, B.-H., Jørgensen, K., Måge, I., Næs, T. LS-PLS: Combining Categorical Design Variables with Blocks of Spectroscopic Measurements. (Submitted)

See Also

[lspls](#), [lsplsCv](#), [orthlspls.fit](#)

plot.lspl

Plots of LS-PLS Models

Description

Plot method for "lspls" objects.

Usage

```
## S3 method for class 'lspls'
plot(x, plottype = c("scores", "loadings"), ...)
## S3 method for class 'lspls'
scoreplot(object, ...)
## S3 method for class 'lspls'
loadingplot(object, ...)
```

Arguments

x, object	Object of class "lspls". The model to be plotted.
plottype	character string. What type of plot to generate.
...	Further arguments, passed on to underlying plot functions.

Details

The plot method simply calls `scoreplot.lspl` or `loadingplot.lspl` depending on the `plottype` argument.

`scoreplot.lspl` gives a series of score plots, one for each PLS model. The user is asked to press Return between each plot.

`loadingplot.lspl` shows a series of loading plots, one for each PLS model. All plots are shown in the same plot window.

Value

The functions return whatever the (last) underlying plot function returns.

Author(s)

Bjørn-Helge Mevik

See Also

[lspls](#), [scoreplot](#), [loadingplot](#), [plot.lsplsCv](#)

Examples

```
##FIXME
```

plot.lsplsCv

Plot Method for Cross-Validations

Description

Plot method for "lsplsCv" objects. It plots the cross-validated (R)MSEP or R^2 against the total number of components or the matrices included in the model.

Usage

```
## S3 method for class 'lsplsCv'
plot(x, which = c("RMSEP", "MSEP", "R2"), ncomp,
      separate = TRUE, scale = !isTRUE(separate), ...)
```

Arguments

x	object of class "lsplsCv". Object to be plotted. Typically the output from lsplsCv .
which	character string. Which measure to plot.
ncomp	list. The number of components to use when plotting, for each PLS matrix in the model. See Details.
separate	logical. Whether separate plots should be generated for each response (default) or one plot with the sum of the measure for all responses.
scale	logical. Whether the responses and predicted values should be divided by the standard deviation of the response prior to calculating the measure. Default is to scale when producing a combined plot (separate = FALSE) and not to scale otherwise.
...	Further arguments, sent to the underlying plot function.

Details

If `ncomp` is not specified, the `plot` method generates a plot of the cross-validated (R)MSEP or R^2 values for all combinations of number of components. The values are plotted against the total number of components. Each point is labelled with the combination of number of components. E.g., for a model with three PLS matrices, '132' means one component from the first matrix, three from the second and two from the third. Also, the lowest (R)MSEP or highest R^2 values for each total number of components are joined by a line.

If `ncomp` is specified, the `plot` method plots (R)MSEP or R^2 for models with the first matrix, with the two first matrices, etc. `ncomp` should be specified as when running `lsplsCv`, and is used for selecting the number of components for each PLS matrix. For instance

```
mod <- lsplsCv(Y ~ X + Z + V:W, ...)
plot(mod, ncomp = list(2, c(1,3)))
```

would plot the RMSEPs for $Y \sim X$, $Y \sim X + Z$ and $Y \sim X + Z + V:W$, using 2, 1 and 3 components for Z, V and W, respectively.

If `separate` is TRUE, a separate plot panel is produced for each response. Otherwise the measure is added for all responses and shown in one plot. If `scale` is TRUE (the default when producing a combined plot), the measures for each response are standardised by dividing the responses and predicted values by the standard deviation of the (corresponding) response prior to calculating the measure. Note that `scale` is ignored when which is "R2" because R^2 is independent of scale.)

Value

The function returns whatever the (last) underlying plot function returns.

Author(s)

Bjørn-Helge Mevik

See Also

[lsplsCv](#), [lspls](#)

Examples

```
##FIXME
```

predict.lspls

Predict Method for LS-PLS Models

Description

Predict method for "lspls" objects. It predicts response values or scores from new data.

Usage

```
## S3 method for class 'lsp1s'
predict(object, newdata, type = c("response", "scores"),
        na.action = na.pass, ...)
```

Arguments

object	object of class "lsp1s". The fitted model to predict with.
newdata	data frame. The new data.
type	character. Whether to predict responses or scores.
na.action	function determining what should be done with missing values in newdata. The default is to predict NA. See na.omit for alternatives.
...	further arguments. Currently not used.

Value

If type = "response", a matrix with predicted response values is returned. If type = "scores", a matrix with predicted score values is returned.

Author(s)

Bjørn-Helge Mevik

See Also

[lsp1s](#)

Examples

```
##FIXME
```

projections

Projection and Orthogonalisation

Description

Functions to project one matrix onto another, or to orthogonalise it against the other.

Usage

```
project(M, N)
orth(M, N)
Corth(M, N)
```

Arguments

M	matrix to be projected or orthogonalised
N	matrix to be projected onto or orthogonalised against

Details

`project(M, N)` calculates the projection of M onto N, i.e., $N(N^t N)^{-1} N^t M$.

`orth(M, N)` orthogonalises M with respect to N, i.e., it calculates the projection of M onto the orthogonal space of N: $M - N(N^t N)^{-1} N^t M$.

`Corth(M, N)` calculates the coefficient matrix needed to orthogonalise future matrices, that is, $(N^t N)^{-1} N^t M$. Future matrices m and n can be orthogonalised with `m - n %*% Corth(M, N)`.

Value

A matrix.

Note

The functions need to be optimised, both for speed and numerical accuracy.

Author(s)

Bjørn-Helge Mevik

See Also

[lspls](#), [lsplsCv](#), [predict.lspls](#)

Examples

```
##FIXME
```

Index

- * **algebra**
 - projections, 14
- * **hplot**
 - plot.lspls, 11
 - plot.lsplsCv, 12
- * **multivariate**
 - lspls, 4
 - lspls-package, 2
 - lsplsCv, 6
 - MSEP.lsplsCv, 8
 - orthlspls.fit, 9
 - orthlsplsCv, 10
 - predict.lspls, 13
- * **package**
 - lspls-package, 2
- * **regression**
 - lspls, 4
 - lspls-package, 2
 - lsplsCv, 6
 - MSEP.lsplsCv, 8
 - orthlspls.fit, 9
 - orthlsplsCv, 10
 - predict.lspls, 13

- Corth (projections), 14
- cvsegments, 7, 8

- loadingplot, 12
- loadingplot.lspls (plot.lspls), 11
- lspls, 2, 3, 4, 7–15
- lspls-package, 2, 4, 6–8
- lsplsCv, 3, 6, 6, 8, 11–13, 15

- MSEP.lsplsCv, 8

- na.omit, 14

- orth (projections), 14
- orthlspls.fit, 5, 9, 11
- orthlsplsCv, 6–8, 10

- plot.lspls, 3, 6, 11
- plot.lsplsCv, 3, 7, 8, 12, 12
- predict.lspls, 13, 15
- project (projections), 14
- projections, 14

- R2.lsplsCv (MSEP.lsplsCv), 8
- RMSEP.lsplsCv (MSEP.lsplsCv), 8

- scoreplot, 12
- scoreplot.lspls (plot.lspls), 11